

# ZW340e

Ultra-compact high brightness laser projector



- **Bright WXGA laser projector - 3600 lumens and IP6X certified**
- **Designed with the environment in mind - DuraCore laser technology cuts power consumption and ensures a long product lifespan**
- **Ultra compact for easy installation - 1.1x zoom, 360-degree and portrait projection**
- **Excellent image quality - Perfect for meeting rooms, medium-sized exhibition venues, events or tradeshows**



The ZW340e is one of Optoma's most compact, hassle free WXGA DuraCore laser projectors to date. This 3600-lumen projector is built for maintenance-free continuous operation up to 30,000 hours, while its small and lightweight footprint makes it 34% smaller than any other projector in the Optoma range, offering flexible installation in virtually any orientation and location.

## Specifications



### Display/image

Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	3,600 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-40°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 140Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.51m ~ 7.62m (20" ~ 300") diagonal

### Lamp info

Light source type	Laser
LASER life	30,000 hours

### Optical

Throw ratio	1.54:1 ~ 1.72:1
Projection distance (m)	39.37 - 393.7
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.85 ~ 24.00
Native offset	112%

### Connectivity

Connections	<b>Inputs</b> 2 x HDMI 1.4a 3D support <b>Outputs</b> 1 x Audio 3.5mm, 1 x USB-A power 1.5A <b>Control</b> 1 x RS232
-------------	--

### General

Noise level (typical)	31dB
Noise level (max)	34dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

### 3D

Full 3D

### Security

Security bar, Kensington Lock, Password protected interface

### IP rating

IP6X

### OSD / display languages

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

### 24/7 operation

Yes

### 360° operation

Yes

### Operating conditions

0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m

### Remote control

Card style

### Speaker count

1

### Watts per speaker

15W

### In the box

AC power cord  
Remote control  
2x AAA batteries  
Basic user manual

### Optional wireless models

QuickCast Pro 4K KIT

### Power

Power supply 100V ~ 240V, 50-60Hz

Power consumption (standby) <0.5W

Power consumption (min) 88W

Power consumption (max) 139W

### Weight and dimensions

Dimensions (W x D x H) 10.79" x 8.5" x 4.49"

Gross weight 9.26 lbs.

Net weight 6.6 lbs.

UPC 796435 44 668 0

