

Specifications

SAMSUNG

Model		QB43C	QB50C	QB55C	QB65C	QB75C	QB85C	
Display Panel	Diagonal Size	43	50	55	65	75	85	
	Class Measured	42.5	49.5	54.6	64.5	74.5	84.5	
	Resolution	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	
	Brightness (Typ.)	350 nit	350 nit	350 nit	350 nit	350 nit	350 nit	
	Orientation	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	
	Haze	2%	2%	2%	2%	2%	2%	
	Contrast Ratio (Typ.)	4,000:1	4,000:1	4,000:1	4,000:1	4,000:1	4,000:1	
	Type	VA	VA	VA	VA	VA	VA	
	Active Display Area	941.184 (H) x 529.416 (V)	1,095.84 (H) x 616.41 (V)	1,209.6 (H) x 680.4 (V)	1,428.48 (H) x 803.52 (V)	1,650.24 (H) x 928.26 (V)	1,872.0 (H) x 1053.01 (V)	
	Pixel Pitch (mm)	0.245 x 0.245	0.285 x 0.285	0.315 x 0.315	0.372 x 0.372	0.429 x 0.429	0.487 x 0.487	
Color Gamut	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%		
Operation Hour	16/7	16/7	16/7	16/7	16/7	16/7		
Connectivity / Sound	Input	Video	HDMI 2.0 (3)	HDMI 2.0 (3)	HDMI 2.0 (3)	HDMI 2.0 (3)	HDMI 2.0 (3)	
		Audio	N/A	N/A	N/A	N/A	N/A	N/A
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
	Output	Video	N/A	N/A	N/A	N/A	N/A	N/A
		Audio	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
		USB	N/A	N/A	N/A	N/A	N/A	N/A
	WiFi / BT	O/O	O/O	O/O	O/O	O/O	O / O	
	External Control	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	
	Speaker	10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch	
	Mechanical Spec	Dimension (mm)	Set	969.5 x 557.8 x 28.5	1,124.1 x 644.8 x 28.5	1,237.9 x 708.8 x 28.5	1,456.8 x 831.9 x 28.5	1,682.3 x 960.4 x 28.5
Package			1,093 x 667 x 126	1,246 x 761 x 131	1,403 x 835 x 148	1,616 x 945 x 164	1,839 x 1,113 x 180	2,077 x 1,222 x 210
Weight (kg)		Set	8.8	11.8	15.7	21.5	33.4	41.9
		Package	11.3	14.9	19.9	28.0	43.5	53.9
VESA Mount		200 x 200	200 x 200	200 x 200	400 x 300	400 x 400	600 x 400	
VESA Mount Screw (Min-Max)		M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	
Bezel Width (mm)	11.5 (Even)	11.5 (Even)	11.5 (Even)	13.4 (Even)	13.4 (Even)	13.9 (Even)		
Features	Key	UHD Signage with Built-in MagicInfoS10, SSSP10.0						
		UHD Signage with Built-in MagicInfoS10, SSSP10.0						
	Internal Player	Operating System	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	
		Processor	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core
	H/W	Storage (FDM)	8GB (3GB available)	8GB (3GB available)	8GB (3GB available)	8GB (3GB available)	8GB (3GB available)	8GB (3GB available)
		2nd Gen. B2B Design Center IR Temperature Sensor Ambient Sensor Auto Level Wi-Fi (2.4/5.0GHz dual) & BT						
	Special	S/W	Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic)					
		Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic)						
	Certification	Safety	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1
		EMC	Class B	Class B	Class B	Class B	Class B	Class A
Environment		ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	
IP Rating		IP5x	IP5x	IP5x	IP5x	IP5x	IP5x	
Security		802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	
Power	Power Supply	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	
	Power Consumption	Max[W/h]	121	132	154	187	214.5	231
		Typical[W/h]	74	82	84	104	129	159
Operating Condition	Temperature	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	
	Relative Humidity	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	
Accessories	Included	Quick Setup Guide, Warranty Card, Power Cord, RS232C (In) Gender Remote Controller & Batteries						
		Optional	Stand Mount	WMN-B505C	WMN-B505C	WMN-B505C	WMN-B505C	WMN-B505C



Crystal UHD Signage

QBC series

Slim design. Stunning performance.

Introducing the QBC series, the slimmest display in the Samsung's UHD signage offerings. This products deliver an unparalleled slim design that fits into any business, while delivering the visual quality to make a big impact. The sleek form factor is easily installed to fit any room design and delivers stunning visual performance. Dynamic Crystal Color and Quantum Processor Lite 4K delivering consistent, lifelike colors to any content. This is not just a display for simple advertising. It's a display that brings the solutions, tools, and picture quality to grow to your business, no matter what industry you're in.

Key features



Ultra Slim Depth

The unparalleled ultra-slim thickness of 28.5mm makes it the thinnest option in Samsung's UHD Signage series. It is compatible with a Slim Fit Wall Mount*, which allows you to install it neatly and easily in any location.

* Slim Fit Wall Mount must be purchased separately.



Even Bezels and Centered VESA Holes

The bezels are even on all four sides of the display for a consistent look, while the central VESA mounting holes ensure secure mounting and easy adjustability to portrait mode.

* The position of the VESA holes may vary slightly by model.



Dynamic Crystal Color

One billion shades of color let you see every subtlety with lifelike color variations. Images are clear and consistent thanks to Samsung's industry leading video processing and upscaling technology.



Smart Calibration

Guarantee complete brand consistency across every location. Using the Samsung mobile app, calibrate displays to showcase brand logos and other collateral in the exact colors.



Energy star / EPEAT Bronze

QBC series has earned an ENERGY STAR 8.0 certification from the Environmental Protection Agency for its energy efficiency and an Electronic Product Environmental Assessment Tool (EPEAT) certification in recognition of its eco-conscious efforts, such as its recycled plastic use.

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Smart Signage

For more information about Samsung Smart Signage, visit www.samsung.com/business

Copyright © 2023 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.
416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea