



# Indoor LED All-in-One

## IAC series

### This is the true all-in-one

Discover a true all-in-one LED display. Experience easier installation than ever with Samsung's exclusive Quick Build technology. Dock the two background plates and hang just four preset modules, and that's it. It only takes two hours to install a giant screen in your space. The IAC series also integrates the control box so it's built into the display, eliminating time-consuming configuration between control box and cabinet. As no additional purchases or components are required, it allows you to focus on getting your display up and running fast. All you have to do is enjoy its brilliant performance. This is Samsung's promise of all-in-one.

\* Install time estimate based on internal testing.

### Key features



#### Quick Build

Samsung's exclusive technology enables a drastically simplified installation taking only two hours to complete a giant 130-inch screen.

\* Install time estimate based on internal testing.



#### Built-in Control Box

The built-in control box eliminates a cumbersome configuration process to get the display up and running faster.



#### All-inclusive Components

From the control box and wall brackets to speakers and deco bezels, every extra peripheral needed to begin operation is included.




#### Brilliant Visuals

The IAC series produces images with vivid color expression, reduced noise and a full range of grays and blacks.



#### HDR

LED HDR turns any content into HDR-level without requiring special metadata.



#### Multi-Screen Connection

Samsung's IAC series allows users to combine multiple displays side by side for simultaneous use, expanding business possibilities for large meeting spaces.

# Specifications

Model		IAC
		130" 2K
Physical Parameter	Pixel Pitch	1.5 mm
	Pixel Configuration	1 red, 1 green, 1 blue
	Configuration (L x H, Per screen)	1,920 x 1,080 pixels
	Diode Type	Surface Mount Device (SMD)
	Dimensions (mm, L x H x D, Per screen)	2,888.5 x 1,628.5 x 56.2 mm (62.2 mm total depth with Wall mount)
	Dimensions (inch, Diagonal x D, Per screen)	130 x 2.2 inch
	No. of Modules (W x H, Per screen)	12 x 9
	Weight (Per screen)	125 kg
Optical Parameter	Brightness (Peak/Max) <sup>(1)</sup>	1,000 nit/500 nit
	Contrast Ratio <sup>(2)</sup>	6,000 : 1
	HDR Compatibility	LED HDR / AI Picture
	Viewing Angle - Horizontal	160°
	Viewing Angle - Vertical	160°
	Bit Depth	16 bit (Internal processing 20bit)
	Color Temperature - Default	6,500K ± 500K (Floating bin)
	Color Temperature - Adjustable	2,800K - 10,000K
Electrical Parameter	Video Rate	50/60 Hz
	Input Power Range	100-240 VAC, 50/60 Hz
	Power Consumption-Max	1700 (W/Screen)
	Power Consumption-Typ	685 (W/Screen)
	Heat Generation-Max	5800 (BTU/Screen)
	Heat Generation-Typ	2337 (BTU/Screen)
	Refresh Rate	3,840 Hz
	Visual Refresh Rate	7,680 Hz
Operational Parameter	Power Redundancy	No
	Working Temperature/Humidity	0°C--40°C/10%-80%RH
	Storage Temperature/Humidity	-20°C--45°C/5%-95%RH
	IP Rating	IP20
Connectivity / Sound	LED Lifetime	100,000 hours
	Controller	Built-in
	Input (Video)	DP 1.2 (1), HDMI 1.4 (3), USB 2.0 (2)
	Output	Audio (Stereo mini Jack)/eARC
	WiFi/BT	O/O
	External Control	RS232C (In), RJ45
	Speaker	10W 2ch
	Safety	62368-1, 60950-1
Certification	EMC	Class A
	Eye-protection	TUV Eye Comfort
	Fire-protection	N/A
Service	Service	Front
	Operating System	Tizen 6.5
Features	MagicINFO	Yes
	Sensor	Temperature, Humidity, Eco Sensor
	Other	AI Picture, LED HDR, Dynamic Peaking
	Other SW Features	Workspace (Microsoft365/VMWare/RDP), Auto Source Switching & Recovery, Dicom Simulation Mode, SmartView+
Accessories	Accessories (In-box)	Décor Frame, Frame Kit, Buffer parts
	Remote Control	IR Remote Cotroller
Package	Box Dimension (mm, W x H x D)	1,840 x 1,847 x 594 (Without pallet) 1,850 x 1,982 x 815 (With pallet)
	Package Weight (Per cabinet)	210 kg
Special Installation	Curve	N/A
	Inclination	N/A
	Rotation	N/A
	Other <sup>(3)</sup>	Side by Side Installation with additional frame kit (Up to 4 screens)

(1) Peak value according to IDMS (Information Display Measurement Standard)  
(2) Measured under 10lux light Test condition. Contrast in darkroom exceeds 1000000:1  
(3) Optional structure required

## About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at [news.samsung.com](https://news.samsung.com).

## Smart Signage

For more information about Samsung Smart Signage, visit [www.samsung.com/business](https://www.samsung.com/business) or [www.samsung.com/displaysolutions](https://www.samsung.com/displaysolutions)

Copyright © 2023 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Austria GmbH  
Praterstraße 31, 1020 Vienna