

## ZH520

Eco-friendly compact high brightness Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -5500 lumens and IP6X certified
- Compact for easy installation 1.3x zoom, 360degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency

The ZH520 is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to TBC% smaller than previous Optoma models.<sup>1</sup>

An added benefit, the ZH520 features an external power supply offering more reliability, portability and energy efficiency.

## **Specifications**

The following specifications are prelin	ninary and subject to change without notice
Display/image	
Display technology	DLP™
Resolution	1080p Full HD (1920x1080)
Brightness	5,500 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction -	30°
horizontal	
Keystone correction - vertical	30°
Displayable colours (millions)	1073.4
Uniformity	75%
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.13:1 ~ 1.47:1
Projection distance	1m - 8m / 39.37" - 314.96"
Zoom	1.3
Zoom type	Manual
• •	ivianuai 16.90 ∼ 21.61
Focal length Native offset	
	116%
Connectivity	
Connections	Inputs 2 x HDMI 2.0
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232, 1 x RJ45
General	
Noise level (typical)	29dB
Noise level (max)	31dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4,25/4,4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-r
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m
Remote control	Card style
	1
Speaker count	I
•	15W
Watts per speaker	
Watts per speaker	15W
Watts per speaker	15W AC power cord Remote Control w/ CR2025 Battery
Watts per speaker In the box	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual
Watts per speaker In the box Optional wireless models	15W AC power cord Remote Control w/ CR2025 Battery
Watts per speaker In the box  Optional wireless models  Power	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual QuickCast Pro 4K KIT
Watts per speaker In the box  Optional wireless models  Power  Power supply	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual QuickCast Pro 4K KIT  External power supply, 100V ~ 240V, 50-60Hz
Watts per speaker In the box  Optional wireless models  Power  Power supply  Power consumption (standby)	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual QuickCast Pro 4K KIT  External power supply, 100V ~ 240V, 50-60Hz <0.5W
Watts per speaker In the box  Optional wireless models  Power  Power supply  Power consumption (standby)  Power consumption (min)	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual QuickCast Pro 4K KIT  External power supply, 100V ~ 240V, 50-60Hz <0.5W 128W
Watts per speaker In the box  Optional wireless models  Power  Power supply  Power consumption (standby)  Power consumption (min)  Power consumption (max)	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual QuickCast Pro 4K KIT  External power supply, 100V ~ 240V, 50-60Hz <0.5W
Watts per speaker In the box  Optional wireless models  Power  Power supply  Power consumption (standby)  Power consumption (min)  Power consumption (max)	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual QuickCast Pro 4K KIT  External power supply, 100V ~ 240V, 50-60Hz <0.5W 128W
Watts per speaker In the box  Optional wireless models  Power  Power supply  Power consumption (standby)  Power consumption (min)  Power consumption (max)  Weight and dimensions	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual QuickCast Pro 4K KIT  External power supply, 100V ~ 240V, 50-60Hz <0.5W 128W
Watts per speaker In the box  Optional wireless models  Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)  Weight and dimensions  Dimensions (W x D x H)	15W AC power cord Remote Control w/ CR2025 Battery  Basic user manual QuickCast Pro 4K KIT  External power supply, 100V ~ 240V, 50-60Hz <0.5W 128W 205W  10.79" x 8.5" x 4.49"
Speaker count Watts per speaker In the box  Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) Gross weight Net weight	15W AC power cord Remote Control w/ CR2025 Battery Basic user manual QuickCast Pro 4K KIT  External power supply, 100V ~ 240V, 50-60Hz <0.5W 128W 205W